



GATOR ROCK BOND AND BINDER KIT KEEPS STONES IN PLACE

TDS Revision Date (dd/mm/yyyy): 25/11/2022



TECHNICAL DATA SHEET

Update:

November 25, 2022

Make sure you have an updated data sheet on hand.

Canada and U.S. dial **1-855-847-7767** or (450) 624-1611

Description:

Mixed **GATOR ROCK BOND** kit is ready to use with 100% washed and dried riverstone, creating a durable permeable and decorative surface. Great for garden pathways where erosion and drainage is a concern.

Ideal For:

- Banding
- Edging and trimming
- Pathways
- Walkways
- Tree wells

Features:

- Porous & permeable.
- Keeps stones in place.
- Reduce maintenance & clean up.
- Durable in extreme conditions

Included In Pail

- Liquid Binding agent (1/2 quart /473ml)
- Riverstone (40 lb/18.2 kg)

APPLICATION INSTRUCTIONS:**PLEASE NOTE :**

- Wear gloves to avoid having binder sticking on your hands. Products should be mixed in a masonry mixer or in a wheelbarrow or on a plywood board.
- For pedestrian use only.
- Works above 60°F (16°C).
- Allow 24 hours to dry without rain.
- All tools used could be cleaned using [Gatorene](#).
- **GATOR ROCK BOND** has a high gloss appearance when first applied, the shine will gradually diminish within 3 months. This will not affect the bonding of the stones.



1800 Berlier st., suite 200, Laval, Quebec, Canada H7L 4S4
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.polybind.com - Email : info@polybind.com



GATOR ROCK BOND AND BINDER KIT KEEPS STONES IN PLACE

TDS Revision Date (dd/mm/yyyy): 25/11/2022



APPLICATION INSTRUCTIONS: (CONT.)



1. A. Always refer to the latest **GATOR ROCK BOND** [Technical Data Sheet \(TDS\)](#) at Polybind.com before installing **GATOR ROCK BOND**.
B. Prepare a solid base by densely compacting 4" (10 cm) of crushed stones.
2. Mix one 1/2 quart (473 ml) container of **GATOR ROCK BOND** with the dry clean riverstone (40 lb/18.2 kg) provided for 4 minutes.
3. Trowel the mixed riverstone on the surface desired, within 20 minutes after mixing.

Coverage Per Kit: 1 kit, at a 1/2" (13 mm) surface thickness, will cover approx. 8 to 10 sq. ft. (0.75 to 0.9 sq. m.)

Storage: Store in a cool, dry, well ventilated area. Store in upright position. Toxic if swallowed. Store at above freezing temperature 32°F (0°C). Shelf life is 1 year in original unopened container.

Packaging:	Product	Size	per Pallet
	Gator Rock Bond and Binder Kit	40 lbs of Rock 1/2 quart (473 ml) of binder	48 kits

WARRANTY:

ALLIANCE DESIGNER PRODUCTS INC. cannot guarantee results as it has no control over surface and sub-surface preparation and product application. **ALLIANCE DESIGNER PRODUCTS INC.** agrees that, if the product is proven to be defective, and on the condition that it was installed pursuant to the method of application of surface and sub-surface preparation described above, then **ALLIANCE DESIGNER PRODUCTS INC.** agrees to refund the purchase price. Proof of purchase is required for any claim. EXCLUSION OF RESPONSIBILITY THE PARTIES AGREE THAT REFUND OF THE PURCHASE PRICE AS STATED IS THE ONLY OBLIGATION OF ALLIANCE DESIGNER PRODUCTS INC. IN ALL EVENTS, **ALLIANCE DESIGNER PRODUCTS INC.**, SHALL NOT BE LIABLE FOR ANY OTHER DAMAGES OR COSTS, DIRECT OR CONSEQUENTIAL. TO THE EXTENT PERMITTED BY LAW, **ALLIANCE DESIGNER PRODUCTS INC.**, EXCLUDES ANY IMPLIED WARRANTY OF QUALITY, MERCHANTABILITY OR FITNESS FOR PURPOSE.



1800 Berlier st., suite 200, Laval, Quebec, Canada H7L 4S4
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.polybind.com - Email : info@polybind.com