



## GATOR ROCK BOND - LIQUID BINDING AGENT KEEPS STONES IN PLACE

TDS Revision Date (dd/mm/yyyy): 25/11/2022



# TECHNICAL DATA SHEET

- Update:** November 25, 2022  
Make sure you have an updated data sheet on hand.  
Canada and U.S. dial 1-855-847-7767 or (450) 624-1611
- Description:** Mixed **GATOR ROCK BOND** with 100% washed and dried riverstone, creates a durable permeable and decorative surface. Great for garden pathways where erosion and drainage is a concern.
- Ideal For:**
- Banding
  - Edging and trimming
  - Pathways
  - Walkways
  - Tree wells
- Features:**
- Porous & permeable.
  - Keeps stones in place.
  - Reduce maintenance & clean up.
  - Durable in extreme conditions

### SUITABLE ROCK TYPES THAT CAN BE USED WITH GATOR ROCK BOND:

- RIVERSTONE • GRANITE • LIMESTONE • MARBLE  
• 1/8" TO 3/8"  
• These rocks have to be clean, free of dust and 100% dry

### APPLICATION INSTRUCTIONS:

- PLEASE NOTE:**
- Rocks have to be clean, free of dust & 100% dry.
  - For pedestrian use only.
  - Works above 60°F (16°C).
  - Allow 24 hours to dry without rain.
  - Wear gloves to avoid having binder sticking on your hands. Products should be mixed in a masonry mixer or in a wheelbarrow or on a plywood board.
  - All tools used could be cleaned using [Gatorene](#).
  - **GATOR ROCK BOND** has a high gloss appearance when first applied, the shine will gradually diminish within 3 months. This will not affect the bonding of the stones.



1800 Berlier st., suite 200, Laval, Quebec, Canada H7L 4S4  
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611  
www.polybind.com - Email : info@polybind.com



## GATOR ROCK BOND - LIQUID BINDING AGENT KEEPS STONES IN PLACE

TDS Revision Date (dd/mm/yyyy): 25/11/2022



### APPLICATION INSTRUCTONS:



1. A. Always refer to the latest **GATOR ROCK BOND LIQUID BINDING AGENT** [Technical Data Sheet \(TDS\)](#) at [Polybind.com](http://Polybind.com) before installing **GATOR ROCK BOND**.  
B. Prepare a solid base by densely compacting 4" (10 cm) of crushed stones.
2. Mix in a ratio of one container (1 US gal.) of **GATOR ROCK BOND** with (320 lbs) of the above mentioned stones for 4 minutes. Mix products automatically with a masonry mixer or you can manually mix on a sheet of plywood or in a wheel barrow.
3. Trowel the mixed riverstone on the surface desired, with a minimal thickness of 1/2" (13 mm) within 20 minutes after mixing.

**Coverage:** One (1) US gal. (3.78 L) mixed with 320 pounds (145 kg) of dry clean stone will cover 80 sq.ft. (7.4 m<sup>2</sup>) at 1/2" (13 mm) thickness.

**Storage:** Store in a cool, dry, well ventilated area. Store in upright position. Store at above freezing temperature 32°F (0°C). Shelf life is 1 year in original unopened container.

Packaging:	Product	Size	per Box	per Pallet
	<b>Gator Rock Bond- Liquid Binding Agent</b>	3.78 L (1 U.S. gal.)	4 units	24 boxes

### WARRANTY:

**ALLIANCE DESIGNER PRODUCTS INC.** cannot guarantee results as it has no control over surface and sub-surface preparation and product application. **ALLIANCE DESIGNER PRODUCTS INC.** agrees that, if the product is proven to be defective, and on the condition that it was installed pursuant to the method of application of surface and sub-surface preparation described above, then **ALLIANCE DESIGNER PRODUCTS INC.** agrees to refund the purchase price. Proof of purchase is required for any claim. EXCLUSION OF RESPONSIBILITY THE PARTIES AGREE THAT REFUND OF THE PURCHASE PRICE AS STATED IS THE ONLY OBLIGATION OF ALLIANCE DESIGNER PRODUCTS INC. IN ALL EVENTS, **ALLIANCE DESIGNER PRODUCTS INC.**, SHALL NOT BE LIABLE FOR ANY OTHER DAMAGES OR COSTS, DIRECT OR CONSEQUENTIAL. TO THE EXTENT PERMITTED BY LAW, **ALLIANCE DESIGNER PRODUCTS INC.**, EXCLUDES ANY IMPLIED WARRANTY OF QUALITY, MERCHANTABILITY OR FITNESS FOR PURPOSE.



1800 Berlier st., suite 200, Laval, Quebec, Canada H7L 4S4  
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611  
[www.polybind.com](http://www.polybind.com) - Email : [info@polybind.com](mailto:info@polybind.com)