



**GATOR WET LOOK SEALER
FOR DRY CAST CONCRETE PAVERS**

TDS Revision Date (dd/mm/yyyy): 01/04/2022

Page 1 of 2

15



TECHNICAL DATA SHEET

Update:

April 1, 2022

Make sure you have an updated data sheet on hand.

Canada and U.S. dial **1-855-847-7767** or (450) 624-1611

Description:

GATOR WET LOOK SEALER is made from acrylic-based polymers. **GATOR WET LOOK SEALER** penetrates deep into the concrete pavers, therefore helps prevent the oil and dirt penetration, corrosion from de-icing salt and the effects from the UV rays. Specifically formulated to be used on unsealed surfaces only.

Features:

- High-gloss
- Vibrant color enhancer
- Joint stabilizer
- Film former
- Easier to clean and maintain
- Solvent-based
- Rain-safe after 90 minutes
- Works between 60°F (16°C) and 85°F (29°C)
- Helps prevent corrosion from de-icing salt, ultraviolet rays effects, motor oil and grease stains

Coverage:

- 1 u.s. gal. (3.78 l) covers 175 ft² (16 m²)

For use on:

For dry cast concrete pavers

Please note:

- Concrete pavers should only be sealed 60 days after their installation date. Consult concrete paver manufacturer's for their recommendation.
- Concrete pavers and jointing sand MUST be 100% dry.
- Temperature should be between 60°F (16°C) and 85°F (29°C) when sealer is applied.
- Concrete paver surface must be cool to the touch when sealer is applied (between 60°F (16°C) and 85°F (29°C)).
- First clean concrete pavers with [GATOR Clean products](#). Remove all oil, grease and rust stains.
- Use [GATOR Efflorescence Cleaner](#) to remove any trapped efflorescence. It also thoroughly cleans the surface to ensure a proper sealer adhesion.
- Use just one (1) layer of sealer.
- When using **GATOR WET LOOK SEALER**, assure yourself at least 48 hours of dry conditions prior to applying the sealer.
- Specifically formulated to be used on unsealed surfaces only. Cannot be used as a resealer.
- Wear protective gloves, eye protection and respiratory protection.
- This sealer is to be employed without thinning or diluting under normal environmental conditions. Use acetone for cleaning. Alliance Designer Products shall not be liable for any non-compliant use.
- Questions? Visit the [Gator Sealer FAQ page](#).



1800 Berlier st., suite 200, Laval, Quebec, Canada H7L 4S4
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.polybind.com - Email : info@polybind.com



GATOR WET LOOK SEALER FOR DRY CAST CONCRETE PAVERS

TDS Revision Date (dd/mm/yyyy): 01/04/2022

Page 2 of 2

15



Application instructions:



Photo 1




Photo 2




Photo 3



Photo 4

1. A. ALWAYS REFER to the latest **GATOR WET LOOK SEALER Technical Data Sheet (TDS)** at Polybind.com before installing **GATOR WET LOOK SEALER**.
B. ALWAYS TEST the product on a small hidden area of approximately 4 sq. ft. (0.4 sq. m.) to ensure the results will meet your expectations.
2. Remove all the stains from the concrete pavers, using **GATOR Clean products**. Use **Gator Clean Sealer Stripper** to remove any unknown coating that remains on the concrete paver surface. (Photo 1)
3. Remove all contaminated jointing material and replace with **Polybind Polymeric Sand**. Follow the instructions on the back of the bags for proper sand installation. (Photo 2)
4. Wait at least 48 hours at a minimum temperature of 60°F (16°C) and no rain for the **Polybind Polymeric Sand** to properly harden.
5. Clean the entire surface with the **GATOR Efflorescence Cleaner**. This product will remove the efflorescence trapped in the concrete paver pores as well as thoroughly clean the surface for proper sealer adhesion.
6. Wait at least 48 hours at a minimum temperature of 60°F (16°C) and no rain so the sand & concrete paver surface are dry. (Photo 3)
7. Best Practice: (See online video. 2 people needed.) Apply one (1) coat of **GATOR WET LOOK SEALER** using a sprayer in 60 sq. ft. sections, then use a solvent-resistant black foam roller to remove the excess sealer left on the surface. (Photo 4)
8. **GATOR WET LOOK SEALER** is water repellant, rain safe after 90 min.
9. Let the sealer dry for 24 hours before using the sealed area.

Packaging:

Product	Retail Size	per Box	per Pallet
GATOR WET LOOK SEALER	3.78 L (1 U.S. gal.)	4 units	24 boxes
GATOR WET LOOK SEALER	18.9 L (5 U.S. gal.)		48 pails

LIMITED WARRANTY:

Before applying the product, the user/buyer must determine its suitability for intended use and user/buyer assumes all risks in that regard. It is a condition of the Limited Warranty that before using the product on the intended larger area, the user/buyer must first test the product on a small less observed area of approximately 4 sq. ft. (0.4 sq. m.) to ensure results meet user/buyer's expectations. In the event that no test is carried out, the Limited Warranty will only apply to 4 sq. ft. (0.4 sq. m.). ALLIANCE DESIGNER PRODUCTS INC. cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation ALLIANCE DESIGNER PRODUCTS INC. is to refund the purchase price. Proof of purchase is required for any claim. ALLIANCE DESIGNER PRODUCTS INC. shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, ALLIANCE DESIGNER PRODUCTS INC. excludes any implied warranty of quality, merchantability or fitness for purpose. The container must at all times be stored at above 32°F (0°C) and away from direct sun to receive the benefit under the Limited Warranty.



1800 Berlier st., suite 200, Laval, Quebec, Canada H7L 4S4
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.polybind.com - Email : info@polybind.com